



Flexible Exhaust Extractor

- central system
- single exhaust fan
- swing arm



Flexible Exhaust extractor is an economical solution for all types of stationary vehicles. The balancer keeps the hose safely off the ground and within reach for ease of use. Multiple extractors connected to a central exhaust fan or by itself makes this fit any service area. The flexible extractor can be mounted on a swing boom for those hard to reach areas. Models for high temperature applications available.

PlymoVent North America:

USA: 115 Melrich Road, Cranbury, NJ 08512
(P)800.644.0911 (P)609.395.3500 (F)609.655.0569
www.plymovent.com, info@plymoventusa.com

Canada: 24-1200 Aerowood Drive, Mississauga, ON L4W 2S7
(P)800.465.0327 (P)905.564.4748 (F)905.564.4609.
www.plymovent.com, info@plymovent.ca

Simple and Affordable

Fixed extractors offers endless solutions to the the individual workplace or large maintenance facility's. The Plymovent Fixed Exhaust Extractor is flexible, easy to install and reliable. Exhaust hoses suitable for all temperature ranges and applications are available. The extractor intended for stationary vehicles can be upgraded according to facility requirements or growth.

An important component to the fixed extractor is the balancer with lock, which automatically keeps the hose lifted off the floor. Several hoses can be one central system.

Plymovents Swinging boom arm is a simple and space saving method of increasing the coverage of the extractor. The double articulating boom extends horizontally up to 8m (25ft) with hose diameters up to 8" dia as a standard. With an assortment of accessories to complete the package.



Complete Product Range



FEF- Fixed Exhaust Extractor with fan

- FUA 1300 -2100 for direct connection to extractor
- single or 3 phase electrical requirements
- comes with wall bracket
- locking balancer with saddle support
- high visibility hose for safety
- various hose types and diameters up to 150mm(6")
- Double Fixed extractor and fan available
- supplied with two 100mm(4") hose
- come with suspension hook or balancer




FEB - Fixed Extractor on Boom Arm

- Horizontal boom lengths up to 8m (25ft)
- High temp hose available up to 200mm(8")
- Articulating horizontal boom for flexibility and covers a wider area
- Complete kits for easy assembly and installation
- Connect to a central fan or optional fan bracket to mount a fan on the wall bracket of the boom
- Microswitch available to control motorized damper or remote start a fan making it an energy saver



FE- Fixed Exhaust Extractor

- fast easy installation
- locking balancer with hose saddle
- wall bracket available
- high visibility hose (yellow and black)
- standard sizes up to 200mm (8")
- hose lengths up to 33' depending on dia.
- low maintenance
- microswitch available
- motorised damper available



Exhaust Extractor Accessories

- Assortment of nozzles available to suit all applications - rubber nozzles up to 600F
- Metal nozzles for higher temperatures
- Pneumatic nozzles for a virtually sealed connection
- An assortment of fans to power any number of extractors
- Hoses to suite any application
- Microswitches, control boxes and motorised dampers to make a smart energy efficient system