

**MERV 8 MEDIA
OFFERED IN
BULK ROLLS
AND PADS**




Tri-Dim Filter Corporation is proud to offer a solution to LEED requirements for a MERV 8 filter at each return grille during construction or major renovation projects¹. TRI-DEK #8 offers MERV 8 efficiency in the convenience and economy of bulk media rolls and pads. Media pads and rolls can be retrofitted to return grilles easier than traditional MERV 8 filters.

TRI-DEK #8 media is constructed of two plies of polyester fibers and is 1-1/4" (32mm) thick with a non-migrating tackifier. The TRI-DEK #8 media is stenciled with "MERV 8" on the downstream side of the media to offer easy visual confirmation of efficiency. TRI-DEK #8 has an initial resistance of 0.33" W.G. (82 PA) at 300 FPM (1.52 m/sec) with a recommended final resistance of 1.0" W.G. (249 PA).


TRI-DEK #8 is an excellent choice for any HVAC application offering unsurpassed efficiency in a bulk media – available in a large number of standard size rolls and cut pads with custom sizes also available. Standard roll lengths are 90 feet, custom roll lengths are available. Tri-Dim also offers the TRI-MET TMZ and TRI-MET TMT pad holding frames for easy and secure use of pad media in HVAC systems.

TRI-DEK #8 offers an innovative, cost-effective solution to the LEED requirements.

Air Flow vs. Resistance (Clean Filter)



Composite Minimum Particle Size Efficiency



¹ = LEED Green Building Rating System For New Construction & Major Renovations, Version 2.2

Additional TRI-DEK® Medias



TRI-DEK #3 = 1-Ply, ¼" Thick, Tackified Media – White – Antimicrobial Treatment optional

TRI-DEK #5 = 1-Ply, ½" Thick, Dry Media – Blue/White – General Purpose Filter Media

TRI-DEK #7 = 1-Ply, 1" Thick, Dry Media – Blue/White – General Purpose Filter Media

TRI-DEK #10 = 1-Ply, 2" Thick, Dry Media – Blue/White – General Purpose Filter Media

TRI-DEK #15/40 = 2-Ply, 1" Tackified Media – Green/White

TRI-DEK #6/15/40 = 3-Ply, 1-¼" Tackified Media – Green/White

TRI-DEK #15/40+3 = 3-Ply, 1-¼" Tackified Media – White/Green/White – Antimicrobial Treatment optional

TRI-DEK #6/15/40+3 = 4-Ply, 1-½" Tackified Media – White/Green/White – Antimicrobial Treatment optional

TRK = 2-Ply, ½" Dry Media – Red/Purple – Designed for Repeated Cleaning – Specialty Media

TRI-DEK® Sleeve Filters

TRI-DEK Sleeve Filters – offers an economical upgrade for fiberglass disposable filters. TRI-DEK Sleeve filters are comprised of a replaceable two-ply heat sealed media sleeve that is pulled over a permanent reusable galvanized wire frame. Replacement media is available in convenient precut pads or economical bulk rolls. Antimicrobial treatment is available as an option.



Tri-Dim Filter Corporation is committed to continual product development – all descriptions, specifications and performance data are subject to change without notice.

Tri-Dim products are manufactured to exacting criteria - there can be a ±5% variance in filter performance.

Tri-Dim® and Tri-Dek® are Registered Trademarks of Tri-Dim Filter Corporation.



TRI-DIM
FILTER CORPORATION

TRI-DIM FILTER CORPORATION
P.O. BOX 466 • 93 INDUSTRIAL DRIVE
LOUISA, VA 23093

(540) 967-2600 • FAX: (540) 967-2835

EMAIL: info@tridim.com • Website: www.tridim.com
TOLL FREE 1-800-458-9835



Local Representation:



#118 - 2677 192nd Street, Surrey, B.C. V3S 3X1
Ph: 604-536-4800 • Fax: 604-536-4830
info@tricanfiltration.com • www.tricanfiltration.com



PLEASE RECYCLE - This paper may not be recyclable in your area if facilities do not exist. This brochure is printed on paper that is certified by the Sustainable Forestry Initiative (SFI) - for more information go to www.sfi-program.org.



BROCHURE #300-1
Revision: 09/07